The **pH/ORP 3000** controller is a micro-processor based instrument with a very sophisticated software yet, very simple to use.

The controller can be used in many applications such as Water treatment, Food industry, Swimming pools, Biotechnology, Waste water and many more.



Software features:

- Temperature readout.
- Calibration parameters display.
- Set-point and alarm conditions display.
- Automatic or manual Temperature compensation.
- Operating mode: automatic and manual.

Electrical and mechanical features:

- 0/20 mA or 4/20 mA programmable isolated output.
- Dual set-points with hysteresis, delay and min/max programmable functions.
- Min/max and set points timing alarm relay.
- EEPROM parameter storage.
- Automatic overload protection and reset
- Extractable terminal blocks.
- ❖ 96X96 (1/4" DIN) housing.

Technical Specifications:

PARAMETER	RANGE/UNITS/DESCRIPTION	
Input	рН	ORP
Units/Range	0-14	+/-1000mv
Resolution	0.01 pH units	1MV
Accurity	+/- 1% of the reading	
Power Supply	110/220 +/- 10 %, 50/60 HZ	
Inputs	pH elect., Antimony, Pt 100	ORP electrode
Temp. Comp.	-10 - 110 deg. C	No T.C
Outputs	4 - SPDT, 5A, dry contact for control, alarm& Auto clean	
Analog Output	1 – Isolated 4-20 Ma for pH or ORP	
Display	LCD, 1X16	
Enclosure	Panel mount, 96X96 housing	

For choosing the electrode, please refer to the electrodes brochures.

Please choose a Pt-100/1000 T.C for this instrument.

For an IP-65 wall mount enclosure, please add the letter E at the end of the P.N.

For a splash proof – clear door, please add the letter D at the end of the P.N.

HEFER SYSTEMS & CONTROLS LTD.

Tel: 972-9-8995069 Fax: 972-9-8995112 E-mail: sales@hefer.co.il Web: www.hefer.co.il